



ACCESSORIES THREADED SCREW CONNECTION M22

cunha  mendes cunha, lda
Equipamentos Industriais

SIGA-NOS EM:



www.facebook.com/CunhaMendesCunhaLda



www.youtube.com/c/CUNHAMENDESCUNHALDA

Zona Industrial do Socorro, Lote
28A 4820-011 São Gens - Fafe
Portugal

Consulte catálogos e promoções em www.cmc.pt

Trigger guns with safety catch | adapters

ACCESSORIES | THREADED SCREW CONNECTION

M2000		
Outlet		M22x1.5 IG
Operating pressure	bar MPa	270 27
Water output	l/min	30
Temperature max.	°C	150



M 2000 - short	
Ord.no.	12491



Starlet - short	
Ord.no.	123271

Starlet		
Outlet		M22x1.5 IG
Operating pressure	bar MPa	250 25
Water output	l/min	40
Temperature max.	°C	150



M2000 - long	
Ord.no.	12480



Starlet - long	
Ord.no.	123202

QUICK RELEASE PLUG-IN SYSTEM

Sophisticated, fast and reliable: the quick release plug-in system with hardened stainless steel components ensures simple and always safe connection of the safety shut-off gun with the lance.

CONVERSION MADE EASY

The previous cleaning accessories with threaded screw connection for existing Kränzle devices is of course still available. However, new high pressure cleaners are now supplied as standard with the innovative quick release plug-in system. A special adapter set allows the problem-free conversion to the new system.



Inlet	M22x1.5 AG
-------	------------



Conversion kit to plug-in system

For converting the Kränzle trigger gun with safety catch with threaded connection to a quick release plug-in system

Attachment plug-in connection	Adapter 1	Adapter 2	Ord.no.
M22x1.5 AG ▶ D12	Quick release insert D12 without anti-twist protection	Quick release insert D12 with anti-twist protection	13455



124415



12440

Adapter threaded screw connection to plug-in system

For the use of Kränzle accessories with threaded screw connection in trigger guns with safety catch with quick release plug-in system

Inlet	Outlet	Anti-twist protection	Length	mm	Ord.no.
Quick release insert D12	M22x1.5 IG	—	100		12441
Quick release insert D12	M22x1.5 IG	●	100		124415
Quick release insert D12	M22x1.5 IG	—	400 with grip plates		12440



Attachment plug-in connection

For conversion of trigger gun with safety catch to quick release plug-in system

Ord.no.	12443
Outlet	D12

Cleaning lances

ACCESSORIES | THREADED SCREW CONNECTION

Inlet	M22x1.5 AG
-------	------------



123922-D2504

Stainless steel lance with flat jet nozzle				
Length	mm	Nozzle size	Spraying angle	Ord.no.
500		without nozzle **	without nozzle **	12393-XXX
500		028	20°	12393-M20028
500		03	20°	12393-M2003
500		042	20°	12393-M20042
500		045	20°	12393-M20045
600		without nozzle **	without nozzle **	123922-XXX
600		035	20°	123922-M20035
600		04	25°	123922-D2504
600		045	25°	123922-D25045
600		05	25°	123922-D2505
600		06	25°	123922-D2506
600		07	25°	123922-D2507



461501

Dirtkiller			
Length	mm	Nozzle size	Ord.no.
500		028	41570-028
500		03	41570-03
500		042	41570-042
500		055	41570-055
500		07	41570-07
600		035	46150
600		045	461501
600		055	461503
600		06	461502



410723

Turbokiller			
Length	mm	Nozzle size	Ord.no.
600		04	41072
600		045	410723
600		05	41580-05
600		055	410724
600		07	410727
600		08	410728
600		10	41580-10
600		11	41580-11



12701-M20042

Stainless steel lance with regulating nozzle				
■ max. 250 bar 25 MPa		■ max. 150 °C		
Length	mm	Nozzle size	Spraying angle	Ord.no.
500		03	20°	12701-M2003
500		042	20°	12701-M20042
500		045	20°	12701-M20045
600		without nozzle **	without nozzle **	12395-XXX
600		03	25°	12395-D2503
600		045	25°	12395-D25045
600		05	25°	12395-D2505
600		07	25°	12395-D2507

12395-D2503



short regulating nozzle	
Ord.no.	132050
Outlet	R 1/4" IG without nozzle **
Length	mm 135



Lances with Vario-Jet			
Length	mm	Nozzle size	Ord.no.
500		03	411568-03
500		042	411568-042
500		055	411568-055

****Please order high-pressure nozzle separately.**



Please indicate the technical data of the high-pressure cleaner when placing your order.

Cleaning lances

ACCESSORIES | THREADED SCREW CONNECTION

Inlet

M22x1.5 AG

kränzle®



Underbody lance

For hard-to-reach areas

Length	mm	Nozzle size	Ord.no.
400		● 07	410751
1000		● 07	41075



Bend lance with handgrip

Infinite adjustment of bending angle from 20° to 140°

Ord.no.	121800-XXX
Length	mm
670	
Outlet	R 1/4" IG, without nozzle **



Double lance with turning hand-grip

Infinite variable control of working pressure

Length	mm	Nozzle size	Ord.no.
660		D3035 **	121311
1000		D3035 **	12131



Double lance with turning knob

Infinite variable control of working pressure


Length	mm	Nozzle size	Ord.no.
660		D3035 **	121316
1000		D3035 **	121317



Lance extension

■ Outlet: M22x1.5 IG

Length	mm	Ord.no.
500	grip plates	150048
1000	grip plates	41154
1250	grip plates	411542
1500	grip plates	411543



Toilet lance

■ with regulating nozzle

Ord.no.	41076
Length	mm
500	
Nozzle size	D25055



**** Low-pressure nozzle serially included. Order high-pressure nozzle separately.**

Floor Cleaners

ACCESSORIES | THREADED SCREW CONNECTION

Inlet	M22x1.5 AG
-------	------------



Round Cleaner UFO short

for small to medium-sized surfaces

Ord.no.		41855
Ø	mm	300
Operating pressure	bar MPa	180 18
Water output max.	l/min	12
Weight	kg	1.9
Nozzle size		045

41850



Round Cleaner UFO long

for small to medium-sized surfaces

Ord.no. without wheels		41850
Ord.no. with wheels		41851
Ø	mm	300
Operating pressure	bar MPa	180 18
Water output max.	l/min	12
Weight	kg	2.2
Nozzle size		045

41851



Round Cleaner UFO long stainless steel

for small to medium-sized surfaces

Ord.no. Nozzle size 045		41861
Ord.no. Nozzle size 055		41860
Ø	mm	350
Operating pressure	bar MPa	210 21
Water output max.	l/min	15
Weight	kg	5.5



Round Cleaner INOX 410

for large to very large surfaces

Ord.no.		41831
Ø	mm	410
Operating pressure	bar MPa	180 18.0
Water output max.	l/min	14
Weight	kg	3.6
Nozzle size		045



Round Cleaner INOX 300

for medium-sized to large surfaces

Ord.no.		41830
Ø	mm	300
Operating pressure	bar MPa	160 16.0
Water output max.	l/min	12
Weight	kg	2.9
Nozzle size		045



Round Cleaner INOX 520

for large to very large surfaces

Ord.no.		41832
Ø	mm	520
Operating pressure	bar MPa	220 22.0
Water output max.	l/min	26
Weight	kg	11.4
Nozzle size		06

Special accessories

ACCESSORIES | THREADED SCREW CONNECTION

Inlet	M22x1.5 AG
-------	------------


kränzle®



Pipe cleaning hose with nozzle

- Operating pressure max.: 200 bar | 20 MPa
- Nozzle size without front bore: KN 055
- other nozzles on request**
- Nozzle size with front bore: KNF 055

Length	m	Ord.no. without front bore	Ord.no. with front bore
10		410581	410581-F
15		41058	41058-F
20		410582	410582-F
25		410583	410583-F
30		410584	410584-F



WITHOUT FRONT BORE

3 jets to the rear



WITH FRONT BORE

3 jets to the rear

1 jet to the front



Cleaning brush flat

Ord.no.	41073
Brush head LxB mm	180x65



410501

Rotating washing brush

Pipe length	mm	Ord.no.
342		410501
1000	grip plates	410505



410500

Cleaning brush transverse

Pipe length	mm	Ord.no.
—		410500
400		128050
1000	grip plates	128052



135301

135311

Foam injector lances

- Production of highly effective foam
- adjustable spraying angle (spot jet - flat-jet)

Container	Liter	Ord.no.
1		135301
2		135311



Universal wall bracket for accessories „Butler“

- for space-saving storage of accessories with threaded screw connection
- Supplied without accessories

Ord.no.	41262
Dimensions LxBxH mm	425x240x280