



GO ROGUE

WITH RULE-DEFYING TIG PERFORMANCE.

BREAK AWAY FROM CONVENTION WITH THE RULE-DEFYING ROGUE.

The days of entry-level mediocrity are over. With unconventional features, unprecedented performance, and an all-new industrial design, Rogue ushers in a new era of welding capability that will force you to rethink everything you expect from a portable TIG machine at this price point. Are you ready to go rogue?

ENTRY-LEVEL PERFORMANCE.

Rogue's next-level technology gives you precise, professional and consistent control for a smooth, stable performance every time. High-frequency TIG start keeps you from experiencing failure on ignition. Advanced TIG controls including gas pre-flow, start current, end current and gas post-flow allow full cycle control to match every application. Monitor and easily control ramp up time and down slope time. Pulse up to 500 Hz for perfect control of heat input.



BASIC POWER.

Throw away your preconceptions about welders in this class = Rogue's power stacks up against machines twice its price. Power Factor Control (PFC) technology allows for a highly efficient and steady arc that is resistant to power fluctuations. With up to 25% duty cycle at 200 A (ET 200IP Pro), Rogue has the strength to crush jobs on thicker materials.

UNDERWHELMING STRENGTH.

No other machine at this price point comes close to matching Rogue's strength. Its robust and rigid fiberglass-molded housing is built to withstand impact after impact, in the shop or in the field. Like every ESAB machine, Rogue comes with our industry-leading three-year warranty for unbeatable peace of mind. Sayonara, cheaply constructed welders.





LIMITED PORTABILITY.

No other machine at this price point comes close to matching Rogue's strength. Its robust and rigid fiberglass-molded housing is built to withstand impact after impact, in the shop or in the field. Rogue is durable and weather resistant, with an IP23S rating for use in tough outdoor applications.

POOR USABILITY.

Rogue's compact and lightweight design makes it easy to carry from job to job. It weighs in at just 8.7 kg (ET180i CE), and its sturdy handle and included shoulder strap make it more comfortable than ever before to go wherever you need to. Plus, its stable arc performance means you can use long extension cables to work in even the most remote locations without affecting weld quality. It is the definition of a portable workhorse.





DELIVERY INCLUDES: power source with 3 m mains cable and plug, shoulder strap, TIG torch SR-B 26 type 4 m, a set of wear parts including tungsten electrode, return cable with clamp 3 m.

SPECIFICATIONS

Model	Rogue ET 180i	Rogue ET 200iP PRO
Primary Voltage 1 ph	230 VAC \pm 15%, 1ph, 50/60 Hz	115/230 VAC \pm 15%, 1ph, 50/60 Hz
Maximum Output	180 A	200 A
Rated KVA	8 kVA	7 kVA
Energy Save Mode	30 W	50 W
Open Circuit Voltage	63 V DC	78 V DC
MMA Welding Output at 20% Duty Cycle	170 A / 26.8V	–
at 25% Duty Cycle	–	200 A / 28.0 V
at 60% Duty Cycle	97 A / 23.9 V	129 A / 25.2 V
at 100% Duty Cycle	75 A / 23.0 V	100 A / 24.0 V
TIG Welding Output at 25% Duty Cycle	180 A / 17.2 V	200 A / 18.0 V
at 60% Duty Cycle	116 A / 14.6 V	129 A / 15.2 V
at 100% Duty Cycle	90 A / 13.6 V	100 A / 14.0 V
Current Range	10 – 180 A	10 – 200 A
Operating Temperature	-10 to +40°C (+14 to +104°F)	-10 to +40°C (+14 to +104°F)
Enclosure Class	IP23S	IP23S
Certification Mark	CE	CE
Dimensions	403 x 153 x 264 mm	403 x 153 x 264 mm
Weight	8.7 kg	9.6 kg

ORDERING INFORMATION

Rogue ET 180i CE	0700500080
Rogue ET 200iP PRO CE	0700500081

OPTIONS AND ACCESSORIES

Description	Part Number
Remote control MMA 4	0700500084
TIG Torch SR-B 26, 4 m	0700025580
TIG Torch SR-B 26, 8 m	0700025581
TIG Torch SR-B 26FX-R, 4 m, Remote	0700025589
TIG Torch SR-B 26FX-R, 8 m, Remote	0700025590
Foot pedal, 4,5 m (15 ft.), 8 PIN	W4014450
Shoulder strap	0700500086
Return cable kit, OKC 50, 3 m	0700006901
Return cable kit, OKC 50, 5 m	0700006885
Electrode holder Handy 200A with 25 mm ² , 3 m, OKC 50	0700006900

Defy convention. Go rogue. Visit WWW.CMC.PT



cunha  mendes cunha, lda
Equipamentos Industriais

email: cmc@cmc.pt web: www.cmc.pt



XA00221820 / GL / EN / 01-2021