

ROAIRVAC R32 1.5

Two stage vacuum pump



+ Versatile

Suitable for refrigerant classes
A1, A2L and A2

+ Strong

Four-pole motor with high torque

+ Compact

Light and small housing for easy
and ergonomic transport

ROAIRVAC R32 1.5



Gas ballast valve

Reduction of water vapour in the oil container, guarantees higher evacuation power and service life

Special filter

Reduces oil mist on exhaust vent

Light and high-quality casing

Protects the integrated components

Ergonomic handle

Light, compact and easy to transport

Removable cable

Prevents cable damage

Integrated vacuum gauge

Simple and fast control of the evacuation process

Integrated solenoid valve

Prevents backwash of oil into the refrigeration system

Four-pole motor

Increased torque and high lifetime



Removable cable and power button for convenient starting procedure



Special filter for reducing oil mist on exhaust vent



Ergonomic handle for easy transport

Technical Data

Power	190W
Final vacuum	15 micron
Inlet	1/4"
Oil capacity	250ml
Refrigerant classes	A1, A2L, A2

Accessories

	
Mineral oil, 1 litre (No. 169200)	Set of 3 pressure hoses (No. 1500000030)

Description



No.

ROAIRVAC R32 1.5

10.1

1000002399